



SUPPLYWAY ULTRA DURABLE FLOOR FINISH



#SW001972

Technical Specifications	
Heel mark resistance	Excellent
Fragrance	Mild
Gloss (ASTM D 1455-87)	1 coat 80 - 85 2 coats 97 - 98
Leveling	Excellent
pH	8.1 - 8.9
Powdering resistance	Excellent
Warranty	2 years

Black Mark Resistant Metal Interlocked Floor Finish

A low odor, black heel mark resistant floor finish that is an exceptional choice for those who want the highest gloss and wear with the least amount of labor. It is nonscuffing, durable, detergent resistant and maintains its high gloss with minimal burnishing, a real labor saver. Ultra Durable is self-sealing, has excellent leveling and is low odor making it easy to apply. Slip resistance meets or exceeds standard, (ASTM D 2047-11) James Machine 0.5 minimum.

Features

- Superior black heel mark resistance
- 2000-3000 square feet/ gallon
- Superior protection for your floor
- Self-sealing

Directions for Use

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces.... **Directions continued on page 2**



SUPPLYWAY ULTRA DURABLE FLOOR FINISH

Directions for Use *(Continued)*

ROUTINE MAINTENANCE

1. Sweep large debris and dust mop
2. Damp mop floor or clean with automatic scrubber and Neutral Floor Cleaner
3. Buff or Burnish floor as needed to enhance shine

RESTORATIVE MAINTENANCE:

1. Completely remove all old wax, finish, and soil from floor surface.
2. Let floor dry completely
3. Apply finish in uniform, thin to medium coats using clean synthetic mop or applicator system
4. Allow floor to dry thoroughly between coats, 30-40 minutes
Coat thickness and humidity may extend dry time
5. Apply a minimum of 4 coats of finish

INTERIM MAINTENANCE:

1. Sweep large debris and dust mop
2. Top scrub floor using an all purpose floor cleaner and a maroon pad to remove top layers of finish
3. Remove any residue and allow floor to dry completely
4. Apply 1-2 coats of finish as directed above

